

ELECTRIC SERIES SCISSOR LIFTS

0608E(2132E)/0808E(2732E)

Complies with ISO/CE/ANSI/CSA/AS/EAC standards

Model	0608E (2132E)	0808E (2732E)
Dimensions		
Max Working Height	8.3m(27'3")	10.1m/8m (33'2"/ 26'3") indoor / outdoor
A Max Platform Height	6.3m(20'8")	8.1m/ 6m (26'7"/ 19'8") indoor/outdoor
B Max Horizontal Extension	0.9m(3')	0.9m(3')
C Length-Stowed	2.46m(8')	2.46m(8')
D Width-Stowed	0.83m(2'9")	0.83m(2'9")
E Height-stowed (Rail Folded)	1.84m(6')	1.96m(6'5")
E Height-stowed (Rail Unfolded)	2.24m(7'4")	2.36m(7'9")
F Wheelbase	1.88m(6'2")	1.88m(6'2")
Ground Clearance(Pothole Guard Stowed)	0.1m(4")	0.1m(4")
Ground Clearance(Pothole Guard Deployed)	25mm(0.98")	25mm(0.98")
Platform Dimensions(LxWxH)	2.3m x 0.8m x 1.1m (7'7" x 2'8" x 3'7")	2.30m x 0.8m x 1.1m (7'6.7" x 2'8" x 3'7")
Performance		
Platform Allowable Occupants(Indoor/Outdoor)	2 persons/1 person	2 persons/1 person
Platform Capacity	380kg(838lbs)	250kg(551lbs)
Drive Speed-Stowed	4km/h(2.5mph)	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)	0.8km/h(0.5mph)
Elevation Time(Unloaded)	25s~30s	30s~35s
Descent Time(Unloaded)	30s~35s	34s~39s
Gradeability	25%	25%
Turning Radius(Inside/Outside)	0/2.1m(0/6'11")	0/2.1m(0/6'11")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	3°/1.5°
Tyre Spec/Type	380x125mm(15x5')/solid	380x125mm(15x5')/solid
Power		
Batteries	6Vx4/225Ah	6Vx4/225Ah
Power Source	24V DC	24V DC
Drive Mode	Motor, front-wheel	Motor, front-wheel
Charger Input	100-240V AC	100-240V AC
Charger Output	30A	30A
Hydraulic Tank Capacity	15L(3.3gal(UK) / 3.9gal(US))	15L(3.3gal(UK)/ 3.9gal(US))
Weight		
Weight	2,090kg(4,608 lbs)	2,265kg(4,994lbs)
Standards Compliance		
ISO/CE/ANSI/CSA/AS/EAC		

