ALL ELECTRIC SCISSOR LIFTS

0608ME ALL (1932ME ALL) / 0808E ALL (2732E ALL)

Compliant with CE/ANSI/CSA standards

Model	0608ME ALL (1932ME ALL)	0808E ALL (2732E ALL)
Dimensions		
Max Working Height (Indoor/Outdoor)	7.8 m (25'7")	10.1 m (33'2") / 8 m (26'3")
A Max Platform Height (Indoor/Outdoor)	5.8 m (19')	8.1 m (26'7") / 6 m (19'8")
B Platform Extension	0.9 m (3')	0.9 m (3')
C Length-Stowed	1.8 m (5'11")	2.46 m (8')
D Machine Width	0.81 m (2'7.9")	0.83 m (2'8.7")
E Height-Stowed (Rails Folded)	1.88 m (6'2")	1.96 m (6'5")
E Height-stowed (Rails Unfolded)	2.14 m (7')	2.36 m (7'9")
F Wheelbase	1.334 m (4'4")	1.88 m (6'2")
Ground Clearance (Pothole Guard Stowed)	0.061 m (2.4")	0.1 m (4")
Ground Clearance (Pothole Guard Deployed)	0.024 m (0.95")	0.025 m (0.98")
Platform Size (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")	2.30 m×0.8 m×1.1 m (6'6.5"×2'7.5"×3'7")
Performance		
Platform Capacity	230 kg (507 lbs)	250 kg (551 lbs)
Extension Deck Capacity	120 kg (265 lbs)	120 kg (265 lbs)
Max Platform Occupants (Indoor/Outdoor)	2 Persons/1 Person	2 Persons/1 Person
Drive Speed (Stowed)	0 ~ 4 km/h (0 ~ 2.5 mph)	0 ~ 4 km/h (0 ~ 2.5 mph)
Drive Speed (Raised)	0 ~ 0.5 km/h (0 ~ 0.3 mph)	0 ~ 0.5 km/h (0 ~ 0.3 mph)
Lift Time (Unloaded)	25 s~30 s	40 s~45 s
Lower Time (Unloaded)	25 s~30 s	40 s~45 s
Gradeability	25%	25%
Max Allowable Inclination (Front-to-Back/Side-to-Side)	3° /1.5°	3° /1.5°
Turning Radius (Inside/Outside)	0 m/1.62 m (0 /5'3.78")	0.61 m (2') / 2.2 m (7'2.6")
Tire Spec/Type	323×100mm (12.7×4")/solid non-marking tires	380×125 mm (15"×5")/solid non-marking tires
Power		
Drive × Steer	2 WD×2 WS	2 WD×2 WS
Drive Motor (V/kW)	24 V AC /0.6 kW	24 V AC/0.7 kW
Battery Capacity	24 V, 220 Ah (AGM Batteries)	24 V, 220 Ah, 20 hr (Lead-acid battery)
Charger (Input/Output)	100 ~ 240V AC/30A	100 ~ 240 V AC/36 A
Weight		
Weight (Indoor/Outdoor)	1,600 kg (3,527 lbs)	2,265 kg (4,994 lbs)
Standards Compliance	CE/ANSI/CSA	CE/ANSI/CSA

We reserve the right to make specification. The above represents the current specifications at time of publications. 6. 2025